

PRE-INCIDENT SURVEY

250 GPM

Building Name: Platinum Auto Survey #: 71Street Address: 5554 LES 264 W

City, State, Zip: _____

Primary Use: office Construction Type: Wood Fram.

Possible Entry: _____

Possible Occupancy: A.M. 1 P.M. _____

Known Handicapped Personnel: _____

NOTIFY IN CASE OF EMERGENCYName: David Spain Name: _____Phone: 974-2000 Phone: _____**BUILDING CONSTRUCTION**Roof Type: Shingle Floor Construction: Wood JoistRoof Construction: Stick Rafter

Basement Construction Type: _____ Height of Basement: _____

Number of Stories: _____ Height of Each Story: _____

Length: 12 Width: 8 Height: 10

Attic Area: _____ Size: L _____ A _____ W _____ A _____ H _____

UTILITY TYPESGas: TenKine Type: L.P.Gas Shut Off Valve Location: @ TankElectric: Garage Utilities Phase: 1

Panel Location: _____

Alarm Location: _____

EXPOSURES

North: _____ FT. West: _____ FT. South: _____ FT. East: _____

Type: _____ Type: _____ Type: _____ Type: _____

SUPPRESSION CRITERIA

Needed Fire Flow: _____ Total Water Supply: _____

Fuel Load: _____ Rate of Flow: _____

HYDRANT LOCATIONS

(1) _____ Flow: _____ Unit: _____

(2) _____ Flow: _____ Unit: _____

(3) _____ Flow: _____ Unit: _____

(4) _____ Flow: _____ Unit: _____

OTHER WATER RESOURCES

(1) _____

(2) _____

(3) _____

SPECIAL RESOURCES

(1) _____

(2) _____

(3) _____

MUTUAL AID

(1) _____ Assignment: _____

(2) _____ Assignment: _____

(3) _____ Assignment: _____

STAGING AREA


Primary: _____

Secondary: _____

MISCELLANEOUS INFORMATION

Sprinkler Connection: _____

Standpipe Connection: _____



© 2012 Google
© 2012 Google

Google earth

Google earth

feet
meters



Platinum Auto.
5554 US 264 W



Structure Name Platinum Auto
 Structure Address 5554 US 26PW

Length	Width	Sq Ft	Sq Root	X 18	X construction type	GPM sum 1	X Occupancy	GPM sum 2
12	8	96	9.80	176.36	1.5	264.54	0.85	224.86

Column F
Fire Resistive 0.6
Non-combustible 0.8
Ordinary 1
Wood Frame 1.5

Column H
.75 if Mostly non-combustible contents
.85 if Limited combustibles (apartments, churches, schools, hospitals)
1.0 if Mostly combustible (restraunts, sheds, garages)
1.15 if Free burning contents (post offices, horse stables, feed mills, repair garages, ag storage)
1.25 if Rapid burning (aircraft hangers, tires, flammable liquids, wood working)

Exposure % add	Exposure add GPM	Exposure per side (75% max) Total Side A	Exposure per side 75% max Side B	Exposure per side 75% max Side C	Exposure per side 75% max Side D	Total GPM with exposures
25%	56.22		0	0	0	224.86
19%	42.72					
14%	31.48					
9%	20.24					
75%	168.65	Total A, B, C, D				
MAX	0					

Column J, K, L and M
If up to 10 feet add 25% per side
If 11 to 30 feet add 19% per side
If 31 to 60 feet add 14% per side
If 61 to 100 feet add 9% per side

Round off to nearest 250 GPM for flows less than 2500 GPM, the nearest 500 GPM over 2500 GPM

Total GPM with exposures	Add 50% for each floor above ground floor	# of floors	Total to add for floors above	Sub-total with floors added	If wood shingles on roof add 500 GPM
250.00	125	0	0.00	250.00	0

FIRE FLOW NEEDED GPM
250.00